3/7/1

DIALOG(R) File 347: JAPIO

(c) 2001 JPO & JAPIO. All rts. reserv.

05560320 **Image available**
PNEUMATIC RADIAL TIRE

PNEOMATIC RADIAL TIKE

PUB. NO.: 09-175120 JP 9175120 A]

PUBLISHED: July 08, 1997 (19970708)

INVENTOR(s): TOMITA ARATA

APPLICANT(s): BRIDGESTONE CORP [000527] (A Japanese Company or Cor

poration)

, JP (Japan)

APPL. NO.: 07-342110 [JP 95342110]

FILED: December 28, 1995 (19951228)

ABSTRACT

PROBLEM TO BE SOLVED: To markedly extend a rejection limit of a tire by

effectively suppressing uneven wearing of a tread shoulder part.

SOLUTION: This tire has a bead core, carcass ply comprising a radial chord

layer, belt comprising one or more chord layers and a tread. In both side

parts of the tread, a peripheral direction main groove 5 extend ed in the

peripheral direction and many cross direction grooves 6, extend ed in the

tire axial direction between the peripheral direction main gro ove and a

tread end part to open one end part to the peripheral direction main groove

and the other end part to a tread end, are provided, an uneve n wearing

preventing block 7, having a tire axial direction width 50% or more the

length of the cross direction groove 6, is provided therein, the tire is

rim-assembled in a standard rim by a regular internal pressur e, when a

regular load is statically loaded, the uneven wearing preventing b lock 7 is

grounded further prevented from coming into contact with a groove side wall

of the cross direction groove 6.